



VIBROSCREEN

Portable screeners

by **VT** | VIBROTECH

A plant that will follow you everywhere



SCM-115T

Up to 4 cubic yards bucket



Great quality, great value !

- 4 wheels drive
- Heavy duty construction
- Portable equipment
- Up to 100 cubic yards per hour
- Built-in grizzly
- Exclusive anti-stall system
- Remote control
- Brush cleaning for the drum

www.vibroscreen.ca

819 362-8871



VIBROSCREEN

Portable screeners

by **VIBROTECH**

MODEL SCM-115T

(Up to 100 cubic yards per hour)

CAPACITY

Maximum single load	Up to 4 cubic yards
Cycle time, average	90 seconds
Trommel dimensions	48" inside diameters x 12'-3"
Screening area	106" x 156" (115 sq-ft)

TOWING

Hitch type	Pintle hook retractable
Axle type	Single axle, double wheels
Suspension	None
Brakes	Electric
Landing gear	Hydraulic
Lights and mud flaps	Included

ENGINE

Manufacturer	Perkins
Type	Diesel, vertical, air cooled
Tank	120 liters (30 gal)
Fuel autonomy	Up to 10 hours
Power	60 HP
Number of cylinders	4
Cold starting aid	Glow plug
Electric starter	Included
Alternator	Included

OPTIONS AVAILABLE

Hydraulic grizzly (included)
Air brake

WEIGHT

Gross	21 900 lbs (9,960 kg)
Tongue	7280 lbs (3310 kg)

HYDRAULICS

Control valves	Trommel (forward - reverse) Front jack cylinder Grizzly (open, close) Fines conveyor (start-stop, open-close)
Flow control	Feeder conveyor (speed control) Trommel (speed control)
Cooling	Hydraulic cooler

WARRANTY

Equipment	12 months
-----------	-----------

WORKING DIMENSIONS

Loading height (without grizzly)	10' - 8"
Loading height (with grizzly)	11' - 2"
Hopper width (feeding)	10' - 6"
Working length	49' - 2"
Discharge belt width	30"

FREIGHT DIMENSIONS

Total height on wheel	11' - 6"
Total length	39' - 6"
Total width	8' - 0"