



VIBROSCREEN

Portable screeners

by **VT** | VIBROTECH

Increase value of your material



SCM-75

Up to 6 cubic yards bucket



Great quality, great value !

- Heavy Duty construction
- Portable equipment
- Up to 300 cubic yards per hour
- Low maintenance
- Reversible shakerhead for better screening effect
- Quick screens change

www.vibroscreen.ca

819 362-8871



VIBROSCREEN

Portable screeners

by **VIBROTECH**

MODEL SCM-75

(Up to 300 cubic yards / hour)

CAPACITY

Maximum single load	Up to 6 cubic yards
Cycle time, average	30 seconds
Shaker head decks	2
Screening area	119" x 90" (75 sq-ft)

TOWING

Hitch type	Fifth wheel
Axle type	Single axle, double wheels
Suspension	None
Brakes	Air
Landing gear	Hydraulic
Lights and mud flaps	Included

ENGINE

Manufacturer	Perkins
Type	Diesel, vertical, water cooled
Tank	84 liters (22 gal)
Fuel autonomy	Up to 10 hours
Power	50 HP
Number of cylinders	4
Cold starting aid	Glow plug
Electric starter	Included
Alternator	Included

OPTIONS AVAILABLE

Wings plates extensions	Steel skirt for wheels
Hydraulic grizzly	Flexmat screen
Wear plate (over's side)	Punch plate (top screen)

WEIGHT

Gross weight	21 641 lbs (9816 kg)
Tongue weight	8541 lbs (3874 kg)

HYDRAULICS

Control valves	Shakerhead (forward - reverse) Front jack cylinder Axle cylinder
Cooling	Hydraulic cooler

WARRANTY

Equipment	12 months
-----------	-----------

WORKING DIMENSIONS

Loading height	11' - 0"
Hopper width (feeding)	12' - 6"
Underneath capacity, bucket width	12' - 6"

FREIGHT DIMENSIONS


Total height on wheel	11' - 11"
Total length	26' - 4"
Total width	8' - 4"



Punch plates (top screen)



Wings plates extensions



Wear plate (over's side)



Steel skirt for wheels